Sl. No.	Description of Items
1	Earthwork excavation by manual means in ordinary soil involving an avera horizontal throw upto 2 meters and an average lift upto 0.5m, excavated s leveled and sides neatly dressed, the disposed earth to be leveled neatly a breaking of clods complete as per specifications.
2	Cleaning the existing black topped surface with brooms, soft brushes an dusting withold gunny bags and / or compressed air to receive bitu bratement including ost of all materials, labour HOM of machineries com per specifications Engineer in charge of the work.
3	Providing and constructing granite / trap / basalt rubble stone mas superstructure with cement mortar 1:8, edges of stones chistle dressed in not less than 20 cms high, bond stones at two m. apart in each course in cost of materials, labour, curing complete as per specifications
4	Providing and laying in position plain cement concrete of nominal mix M 7 OPC cement @ 180 kgs. With 40mm and down size graded granite metal aggregates @ 0.85cum and fine agggegate @ 0.57cum machine mixed, co laid in layers not exceeding 15cms thick, well compacted in foundation and cost of all materials, labour HOM of machinery curing complete specifications.
5	Providing and removing centering shuttering strutting, propping etc., and s of form work for vertical surface such as walls at any thickness, including pilasters, buttresses, plinth and string courses cost of all materials, complete as per specifications.
6	Providing and laying in position plain cement concrete of mix M 1:2:4 with @ 240 kgs, with 20mm and down size graded granite metal coarse aggre 0.878cum and fine aggregates @0.459cm machine mixed, conrete laid not exceeding 15cms, thick, well compacted in foundation and plinth, and cost of materials, labour HOM of machinery curing complete as epr specifica